

EP-12 motor performance

US	Patent	Number	8 912	69

Boat size ranges	20' - 35'
Comparable gas/petrol rating	12 h.p.
Suggested horsepower replacement range	8 - 18 h.p.
Peak kW	8.8 kW
Continuous kW	5.1 kW
Miles per gallon equivalency	65 mpg
Length	21"
Width	16.22"
Height	18.32"
Weight	260 lbs

E-POWER ELECTRIC PERFORMANCE

Cruising speed*	5 - 6.5 knots
Cruising time*	7 - 3 hours
Cruising range*	33 - 19 nm
Recharging time standard charger*	3 - 4 hours
Recharging time quick charger*	2 - 3 hours
Number of 12 volt 8-D batteries (245 Ah)	4 batteries
Battery bank voltage in total	48 vdc
Amps (maximum)	106 amps
Kilowatts (peak output kW rating)	8.8 kW
Kilowatts (continuous output kW rating)	5.1 kW
Charger	Elcon PFC 1500
Quick charger (optional)	Elcon PFC 2000

E-POWER HYBRID ELECTRIC PERFORMANCE: OPTIONAL GENERATOR

Genset kilowatt size (AC OR DC CONTINUOUS OUTPUT KW RATING)*	1.5 - 3 kW	
Typical fuel tank capacity for genset (gallons)	15 gal	
Cruising speed*	5 - 6.5 knots	
Cruising time*	81 - 48 hours	
Cruising range*	405 - 306 nm	
Number of 12 volt 8-D batteries (245 Ah)	4 batteries	
Battery bank voltage	48 vdc	
Charger(s) required	1 charger	

SPOWER ELECTRIC HYBRID

*Actual performance may vary based on operating conditions, figures above when traveling between 60-80% of hull speed. **Shore power-50% depth of discharge
To convert from nautical miles (nm) to statute miles multiply nm by 1.15. With Electric Hybrid system additional kilowatts should be added depending on house loads (1,000 watts equals 1kW)





